

AK后备式系列

Line Interactive UPS AK650-2000VA



功能 FUNCTIONS

- 简洁、小巧、大方的外观 Small and delicate
- 超宽市电输入范围 Wide input voltage range
- 卓越的微处理器确保可靠运行 Excellent microprocessor ensures operation
- 自动调节市电升压，降压 Automatic voltage regulation
- 市电自动重启功能 Automatic restart function for utility power
- 输出模拟正弦波 Simulated sine wave

应用范围 APPLICATIONS

- 个人电脑 Personal computer
- 打印机 Printer
- POS机 POS(Point of sales) terminals
- 安保系统 Security system
- 传真机 Fax machine
- 交换机,路由器 Modem , router

型号 Model		AK650	AK850	AK1000	AK1200	AK1500	AK2000
安装方式 Installation method		塔式 Tower type UPS					
输入制式 Main topology		L+N+PE					
容量 Capacity		650VA/390W	850VA/510W	1000VA/600W	1200VA/720W	1500VA/900W	2000VA/1200W
输入 Input							
输入电压 Input voltage		110/120VAC or 220/230/240VAC					
电压范围 Voltage range		86-140VAC or 170-285VAC					
输入频率 Input frequency		50/60Hz					
功率因数 Factor		≥0.999					
输出 Output							
输出制式 Main topology		L+N+PE					
输出电压 Output voltage		110/120VAC or 220/230/240VAC					
电压范围 (电池模式) Voltage range (battery mode)		±10%					
输出频率 (同步校正范围) Frequency synchronous range		50Hz or 60Hz ± 1Hz					
功率因数 Factor		0.6					
转换时间 Transfer time		6ms					
输出波形 Output waveform		模拟正弦波 Simulated sine wave					
通讯与管理 Communication and Management							
通讯接口 Communication interface		RS232/USB/RJ11/RJ45					
控制面板 Control panel		多功能LCD，状态和显示控制台 Multi functional LCD, status and display console					
标机 Standard UPS							
标机电池 Standard UPS battery	电池类型 Battery type	铅酸 VRLA					
	充电电流 Charging current	1A					
	电池电压 Battery voltage	12V			24V		
	电池容量 Battery capacity	7AH	9AH	9AH	7AH	9AH	9AH
机器尺寸 Machine data	尺寸 Size (MM)	330*100*150			365*140*165		
	重量 Weight (KG)	5.2KG	5.7KG	5.8KG	11.9KG	12.6KG	17KG
装箱数据 Packing data	尺寸 Size (MM)	390*313*440			450*436*250		
	重量 Weight (KG)	20.8KG	22.8KG	23.2KG	23.8KG	25.2KG	34KG
	UPS数量 UPS Number	4			2		
环境 Environment							
运行湿度 Operating humidity		20%~95% (No condensing) 无凝露					
相对温度 Relative temperature		'-25~55℃					
最大噪音值满载 (1m处) Maximum noise level at full load (at 1m)		<40dBA@1M					

现行产品规格若有变更不再另行通知 Products specifications are subject to change without further notice