

Winner Pro机架式UPS 1KVA-10KVA

Rack-mounted UPS 1KVA-10KVA



功能FUNCTIONS

- 真正实现在线双转换 Truly achieve online double conversion
- 微处理器控制确保高可靠性 Microprocessor control ensures high reliability
- 输入功率因素校正 Input power factor correction
- 输出功率因素可达0.8 Output power factor up to 0.8
- 宽市电输入范围(110V-300V) Wide utility input range (110V-300V)
- 高效的变频转换模式 Efficient frequency conversion mode
- 兼容发电机 Compatible with generators
- 长效机型充电电流达6A External battery ups charging current up to 6A

应用领域APPLICATIONS FIELDS

广泛应用于网络管理中心和计算机中、,银行证券、税务、通信、邮政、广电、公安、交通、电力、医疗、工业控制、国防等重要数据领域

Widely used in network management centers and computers, banks, securities, taxation, communications, postal services, radio and television, public security, transportation, electric power, medical, industrial control, national defense and other important data fields.

型号Model		C1KR(S)		C2KR(S)		C3KR(S)		C6KR(S)		C10KR(S)	
相位 Phase		单相 Single phase									
容量 Capacity		1KVA/800W		2KVA/1600W		3KVA/2400W		6KVA/4800W		10KVA/8000W	
输入 Input											
输入电压 Input voltage		100/110/115/120/127VAC或200/208/220/230/240VCA						208/220/230/240VAC			
电压范围 Voltage range		55-145VAC/110-300VAC@50% load负载 85-140VAC/160-280VAC@100% load负载						110-300VAC±3%@50% load负载 176-300VAC±3%@100% load负载			
输入频率 Input frequency		40Hz-70Hz						46-54Hz或56-64Hz			
功率因数 Factor		≥0.99@100% load负载									
输出 Output											
输出电压Output voltage		100/110/115/120/127VAC或200/208/220/230/240VCA						208/220/230/240VCA			
电压范围（电池模式） Voltage range (battery mode)		±1%									
输出频率（同步校正范围） Frequency synchronous range		47-53Hz/57-63Hz						46-54Hz/56-64Hz			
频率范围（电池模式） Frequency range (battery mode)		50Hz±0.25Hz/60Hz±0.3Hz						50Hz/60Hz±0.1Hz			
峰值系数 Peak factor		3:01									
谐波平衡度Waveform balance		≤3%THD (Linear load 线性负载) ≤6%THD (Nonlinear load非线性负载)						≤3%THD (Linear load 线性负载) ≤5%THD (Nonlinear load非线性负载)			
转换时间 Conversion time		0ms									
输出波形 Output waveform		纯正弦波 Pure sine wave									
效率 Efficiency											
市电模式 Mains power mode		92%		92%		92%		92%		93%	
电池模式 Battery mode		90%		90%		90%		90%		91%	
电池 Battery											
标机 Standard UPS	电池型号 Battery model	12V/7AH						12V/9AH			
	电池数量 Battery quantity	2		4		6		16	20	16	20
	充电时间 charging time	4小时充至90% Charge to 90% in 4 hours						9小时充至90% Charge to 90% in 9 hours			
	最大充电电流Maximum charging current	1.0A (Max)						1A/2A (adjustable)			
	充电电压 Charging voltage±1%	27.4VDC		54.7VDC		82.1VDC		218.4VDC	273VDC	218.4VDC	273VDC
长效机 External battery UPS	电池型号 Battery model	取决于申请商 Depending on the applicant									
	电池数量 Battery quantity	2	3	4	6	8	6	8	16-20（可调整 adjustable）		
	最大充电电流Maximum charging current	1.0A/2.0A/4.0A/6.0A						1A/2A/4A/6A（可调整 adjustable）			
	充电电压 Charging voltage±1%	27.4VDC	41VDC	54.7VDC	82.1VDC	109.4VDC	82.1VDC	109.4VDC	218.4VDC±1%（基于16颗电池） (Based on 16pcs batteries)		
显示说明 Display description											
LCD		负载大小，电池容量，市电模式，电池模式，旁路模式，故障指示 Load size, battery capacity, municipal power mode, battery mode, bypass mode, fault indication									
物理性能											
标机 Standard UPS	尺寸 Size（MM）	310*438*88		410*438*88		630*438*88		主机ups: 500*438*88 电池 battery: 668*438*88	主机ups: 500*438*88 电池battery: 668*438*133	主机ups: 580*438*133 电池battery: 580*438*133	
	重量 Weight（KG）	10		17		25.6		ups: 15 battery: 48	ups: 15 battery: 61	ups: 18 battery: 51	ups: 18 battery: 61
长效机 External battery UPS	尺寸 Size（MM）	310*438*88		410*438*88				500*438*88		580*438*133	
	重量 Weight（KG）	5.6		8.6				13		17	
使用环境 Working environment											
湿度 Humidity		20-90%RH@0-40℃(不结露No condensation)									
噪音 Noise		<50dBA@1m									
控制管理 Control management											
智能Intelligent RS-232/USB		支持Support Windows®2000/2003/XP/Vista/2008，Windows®7/8，Linux，MAC									
可选Optional SNMP		电源管理支持SNMP管理与网络管理Power management support SNMP and network management									