

高频在线式系列单进单出 三进单出 6KVA-30KVA
 High Frequency Online Single Input Single Output
 Three Input Single Output UPS 6KVA to 30KVA



功能FUNCTIONS

- 真正实现在线双转换 Real-time Dual Conversion
- 微处理器控制确保高可靠性 Microprocessor control ensures high reliability
- 输出功率因可达0.9 Power factor up to 0.9
- 宽市点输入范围(110V-300V) Wide input voltage range(110V-300V)
- 输出正弦波，兼容发电机 Output sine wave,compatible with generators
- 选配的精致SNMP卡能单独 Optional SNMP card for independent
或RS232一起完美监控 or seamless monitoring with RS232

应用领域APPLICATIONS FIELDS

广泛应用于网络管理中心和计算机中、,银行证券、税务、通信、邮政、广电、公安、交通、电力、医疗、工业控制、国防等重要数据领域

Widely used in network management centers and computers, banks, securities, taxation, communications, postal services, radio and television, public security, transportation, electric power, medical, industrial control, national defense and other important data fields.

型号Model	SP6K(S)	SP10K(S)	3C10K(S)	3C15K(S)	3C20K(S)	3C30K(S)
相位Phase	Single-input single-output		Three-input single-output			
容量Capacity	6KVA 5400W	10KVA 9000W	10KVA 8000W	15KVA 12000W	20KVA 16000W	30KVA 24000W
输入Input						
输入电压Input Voltage	208/220/230/240VAC		380/400VAC/415VAC (3ph + N)			
电压范围Voltage range	110-300VAC @ 50% load 负载 176-300VAC @ 100% load 负载		190-520VAC (3-phase + N) @ 50% load 负载 305-520VAC (3-phase) @ 100% load 负载			
输入频率Input Frequency	46~54Hz or 56~64Hz					
功率因数Power Factor	≥0.99@100% load		≥0.8@100% load			
输出Output						
输出电压Output Voltage	208/220/230/240VCA					
稳压精度AC voltage regulation	±1%					
输出频率（同步校正范围） Frequency (Synchronous correction range)	46-54Hz/56-64Hz					
频率范围（电池模式） Frequency Range (Battery Mode)	50Hz/60Hz±0.1Hz		50Hz/60Hz±0.2Hz			
峰值系数Surge Rating	3:1(最大max)		3:1(最大max)			
谐波平衡度Waveform balance	≤3% THD (Linear Load 线性负载) ≤5% THD (Non-linear Load 非线性负载)					
转换时间Transfer Time	0ms					
输出波形Output Waveform	纯正弦波 Pure Sine Wave					
效率Efficiencies						
市电模式 Mains Mode	93%	94%	91%	91%	93%	91%
电池模式Battery Mode	90%	91%	91%	91%	92%	90%
电池Battery						
标机 Standard UPS	电池型号Battery Model	12V/7AH				
	电池数量Battery quantity	16	16	16/20	16/20	16/20
	充电时间Charging time	9小时充至90% 9 hours to 90% full capacity				
	最大充电电流 Max Charging Current	预设Preset1A，可调1A/2A 4A adjustable				
	充电电压 Charging voltage	218.4VDC±1%/273VDC±1%				
长效机 External battery UPS	电池型号Battery Model	取决于申请商 Depends on the applicant				
	电池数量Battery quantity	16-20 adjustable（可调整）				
	最大充电电流 Max charging current	1A/2A/4A/6A adjustable（可调整）	可预设Preset 4A, 可调整1A/2A/4A adjustable			
	充电电压 Charging voltage	218.4VDC±1% , 273VDC±1%				
显示说明 Display Instructions						
LCD	负载大小，电池容量，市电模式，电池模式，旁路模式，故障指示 Load size, battery capacity, mains mode, battery mode, bypass mode, fault indication					
物理性能 Physical performance						
标机 Standard UPS	尺寸Size（MM）	500*248*616		500*248*620		
	重量Weight（KG）	57	68			
长效机 External battery UPS	尺寸Size（MM）	500*248*460		575*248*620		
	重量Weight（KG）	18	20	27	35	35
使用环境Usage environment						
湿度Humidity	20-95%RH@0-45℃（No condensation 不结露）					
噪音Noise	<60dbA@1M					
控制管理Control Management						
智能 Smart RS-232/USB	支持Supports Windows® 2000/2003/XP/Vista/2008, Windows® 7/8, Linux, and MAC					
可选 Optional SNMP	电源管理支持SNMP管理与网络管理 Power management supports SNMP management and network management					